

# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

### **SECTION 1. IDENTIFICATION**

Product name : Freon™ 134a (HFC-134a) Refrigerant - Propellant

SDS-Identcode : 130000000349

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19899 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant

Restrictions on use : For professional and industrial installation and use only.

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Gases under pressure : Liquefied gas

Simple Asphyxiant

**GHS** label elements

Hazard pictograms :

 $\Diamond$ 

Signal Word : Warning

Hazard Statements : H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary Statements : Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

#### Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture Substance

Substance name 1,1,1,2-Tetrafluoroethane

CAS-No. 811-97-2

### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane*	811-97-2	100

<sup>\*</sup> Voluntarily-disclosed non-hazardous substance

#### **SECTION 4. FIRST AID MEASURES**

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact Thaw frosted parts with lukewarm water. Do not rub affected

Get medical attention immediately.

In case of eye contact Get medical attention immediately.

If swallowed Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and

delayed

Contact with liquid or refrigerated gas can cause cold burns

and frostbite.

May cause cardiac arrhythmia.

Other symptoms potentially related to misuse or inhalation

abuse are

Cardiac sensitization Anaesthetic effects Light-headedness

Dizziness confusion

Lack of coordination

**Drowsiness** Unconsciousness

Protection of first-aiders No special precautions are necessary for first aid responders.



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Hydrogen fluoride carbonyl fluoride

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Evacuate personnel to safe areas.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Retain and dispose of contaminated wash water.

Methods and materials for

containment and cleaning up

Ventilate the area.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### **SECTION 7. HANDLING AND STORAGE**



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Technical measures : Use equipment rated for cylinder pressure. Use a backflow

preventative device in piping. Close valve after each use and

when empty.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid breathing gas.

Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure

assessment

Wear cold insulating gloves/ face shield/ eye protection. Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet

piped to use point.

Use a check valve or trap in the discharge line to prevent

hazardous back flow into the cylinder. Prevent backflow into the gas tank.

Use a pressure reducing regulator when connecting cylinder

to lower pressure (<3000 psig) piping or systems.

Close valve after each use and when empty. Do NOT change

or force fit connections.

Prevent the intrusion of water into the gas tank.

Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders.

Use a suitable hand truck for cylinder movement.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Cylinders should be stored upright and firmly secured to

prevent falling or being knocked over.

Separate full containers from empty containers.

Do not store near combustible materials.

Avoid area where salt or other corrosive materials are present.

Keep in properly labeled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable liquids Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

**Explosives** 

Acutely toxic substances and mixtures Substances and mixtures with chronic toxicity



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Recommended storage tem- : < 52 °C

perature

Storage period : > 10 y

Further information on stor-

age stability

: The product has an indefinite shelf life when stored properly.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
1,1,1,2-Tetrafluoroethane	811-97-2	TWA	1,000 ppm	US WEEL

**Engineering measures** Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection General and local exhaust ventilation is recommended to

> maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material Low temperature resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

> on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the

product. Change gloves often!

Eye protection Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

Face-shield



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Skin and body protection : Skin should be washed after contact.

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance : Liquefied gas

Color : colorless

Odor : slight, ether-like

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : -108 °C

Initial boiling point and boiling

range

-26 °C

(1,013 hPa)

Flash point : Not applicable

Evaporation rate : > 1

(CCL4=1.0)

Flammability (solid, gas) : Will not burn

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper

flammability limit

Upper flammability limit

Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit

Method: ASTM E681

None.

Vapor pressure : 5,700 hPa (20 °C)

Relative vapor density : No data available

Relative density : 1.208 (25 °C)

Density : 1.21 g/cm<sup>3</sup> (25 °C)

(as liquid)

Solubility(ies)



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Water solubility : 1.5 g/l (25 °C)

Partition coefficient: n-

octanol/water

: log Pow: 0.025 (25 °C)

Autoignition temperature : > 743 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable if used as directed. Follow precautionary advice and

avoid incompatible materials and conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Skin contact Eye contact

### **Acute toxicity**

Not classified based on available information.

## **Ingredients:**

### 1,1,1,2-Tetrafluoroethane:

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm

Exposure time: 4 h Test atmosphere: gas

No observed adverse effect concentration (Dog): 40000 ppm



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Test atmosphere: gas

Symptoms: Cardiac sensitization

Lowest observed adverse effect concentration (Dog): 80000

maa

Test atmosphere: gas

Symptoms: Cardiac sensitization

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m<sup>3</sup>

Test atmosphere: gas

Symptoms: Cardiac sensitization

### Skin corrosion/irritation

Not classified based on available information.

### **Ingredients:**

### 1,1,1,2-Tetrafluoroethane:

Species: Rabbit

Result: No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### **Ingredients:**

### 1,1,1,2-Tetrafluoroethane:

Species: Rabbit

Result: No eye irritation

### Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

# Ingredients:

### 1,1,1,2-Tetrafluoroethane:

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Species: Rat Result: negative

### Germ cell mutagenicity

Not classified based on available information.



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

### **Ingredients:**

1,1,1,2-Tetrafluoroethane:

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified based on available information.

**Ingredients:** 

1,1,1,2-Tetrafluoroethane:

Carcinogenicity - Assess-

ment

: Weight of evidence does not support classification as a car-

cinogen

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

**Ingredients:** 

1,1,1,2-Tetrafluoroethane:

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for

reproductive toxicity

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

1,1,1,2-Tetrafluoroethane:

Assessment: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Ingredients:

1,1,1,2-Tetrafluoroethane:

Species: Rat



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

NOAEL: 50000 ppm LOAEL: > 50000 ppm

Application Route: inhalation (gas)

Exposure time: 90 d

Method: OECD Test Guideline 413

Remarks: No significant adverse effects were reported

**Aspiration toxicity** 

Not classified based on available information.

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### Ingredients:

# 1,1,1,2-Tetrafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 980 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (algae): 142 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2

mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

### Persistence and degradability

### Ingredients:

### 1,1,1,2-Tetrafluoroethane:

Biodegradability : Result: Not readily biodegradable.

### Bioaccumulative potential

### **Ingredients:**

### 1,1,1,2-Tetrafluoroethane:

Partition coefficient: n-

log Pow: 1.06

octanol/water

### Mobility in soil

No data available



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

#### Other adverse effects

**Product:** 

Results of PBT and vPvB

assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be

very persistent and very bioaccumulating (vPvB).

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

**UNRTDG** 

**UN** number UN 3159

Proper shipping name 1,1,1,2-TETRAFLUOROETHANE

Class 2.2

Packing group Not assigned by regulation

Labels 2.2

IATA-DGR

UN/ID No. UN 3159

Proper shipping name : 1,1,1,2-Tetrafluoroethane

Class

: Not assigned by regulation Packing group Non-flammable, non-toxic Gas Labels

Packing instruction (cargo 200

aircraft)

Packing instruction (passen-

200

ger aircraft)

**IMDG-Code** 

**UN** number UN 3159

Proper shipping name 1,1,1,2-TETRAFLUOROETHANE

Class 2.2

Packing group Not assigned by regulation

Labels 2.2 EmS Code F-C, S-V Marine pollutant no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

**49 CFR** 

UN/ID/NA number : UN 3159

Proper shipping name : 1,1,1,2-Tetrafluoroethane

Class : 2.2

Packing group : Not assigned by regulation Labels : NON-FLAMMABLE GAS

ERG Code : 126 Marine pollutant : no

# **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Gases under pressure

Simple Asphyxiant

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **US State Regulations**

# Pennsylvania Right To Know

1,1,1,2-Tetrafluoroethane

811-97-2

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.




# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Freon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors. All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

US WEEL / TWA : 8-hr TWA

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DOT - Department of Transportation: DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse)



# Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version Revision Date: SDS Number: Date of last issue: 11/22/2017 9.0 02/06/2018 1325513-00037 Date of first issue: 02/27/2017

Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

**Data Sheet** 

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 02/06/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8